




EXC2310




EXC2303




EXC2307




EXC2316




EXC2372




EXC2374




EXC2373




EXC2384




EXC2361




EXC2362




EXC2381




EXC2382




EXC2311



EXC2312



EXC2313



EXC2379

SR Classic EXCELLENCE

Homogeneous sheet Flooring

Description



















High Specification R9 Resilient Homogeneous Flooring
 Suitable for use in all Dry areas: Clean Rooms, Hospitals,
 Offices, Shopping Malls, Factories and Schools
 Available in 2.0 thickness



1 PUR Treatment
 2 Single Homogeneous
 Layer

Technical

SR Classic EXCELLENCE is available with the following performance attributes. Please advise your specific requirements so we can offer the corresponding performance level product for your needs

Overall Thickness		GB/T 11982.2 2015	2.0mm
Wear Resistant Layer Thickness		GB/T 11982.2 2015	0.35mm/0.55mm/0.7mm
Roll Dimensions - width		GB/T 11982.2 2015	2.0m
Roll Dimensions - length		GB/T 11982.2 2015	20m
Total Weight		GB/T 11982.2 2015	2900g/m ²
FIRE Performance		GB8624-2012	B1
SLIP RESISTANCE		DIN 51130-2014	R9
Residual Indentation		GB/T11982.2-2015	PASS
Wear Resistance		GB/T11982.2-2015	T LEVEL
Heating Warpage		GB/T11982.2-2015	PASS
Dimensional Stability		GB/T11982.2-2015	PASS
Hazardous Substances Limit		GB18586-2001	PASS
Chemical Resistance		EN423:2002	PASS
Antibacterial Properties		ISO 22196:2011	PASS
Colour Fastness		GB/T11982.2-2015	Conforms with Standard
Seam Strength		GB/T11982.2-2015	Conforms with Standard
Pollution Resistance		GB/T11982.2-2015	O Level
Castor Chair Test		GB/T11982.2-2015	No Damage

Precautions

FloorXL products are not suitable for areas subjected to regular and extended exposure to rubber matting, certain solvents, organic dyes or floor maintenance products containing pine oil. Contact with rubber tyres and lighted cigarette butts may also damage the products. For further details please check our Installation/maintenance Guides or contact your FloorXL representative