



SR Classic RUBBER


Homogeneous Rubber Flooring




SCR6201



SCR6202




SCR6203



SCR6204



SCR6205




SCR6206




SCR6207




SCR6208




SCR6112




SCR6113




SCR6114




SCR6115




SCR6116



SCR6117



SCR6118



SCR6119

SR Classic RUBBER

Homogeneous Rubber Flooring

Description












High Specification R9 Resilient Rubber Flooring
 Suitable for use in all Dry and Wet areas in Public spaces, Factories, Commercial Buildings, Schools, Airports and Hospitals
 Available in following format:
 SCR6201 to SCR6208 = Sheet 1.22m x 15m in 2.0, 3.0 and 3.5mm thickness
 SCR6112 to SCR6119 = Tile 1m x 1m in 3.0 and 3.5mm thickness

Warranty

The flooring Warranty period is subject to specific use and to the products being specified, installed and maintained in accordance with our recommendations (copies available on request)
 Please provide details so we can confirm

Technical

SR Classic RUBBER is available with the following performance attributes. Please advise your specific requirements so we can offer the corresponding performance level product for your needs

Dimensional Stability		EN434:1994	PASS
Residual Indentation		EN434:1994	PASS
Wear Resistance		ISO 4649:2017	PASS
SLIP RESISTANCE		Din 51130:2014	R9
Curl		EN434:1994	PASS
Flexibility		EN434:1994	PASS
Stain Resistance		EN ISO 26987: 2012	PASS
Colour Fastness		EN ISO 105-B02:2014	PASS
FIRE Performance		GB8624-2012	B1
Resistance to Cigarette Burn		EN 1399:1997	PASS
Content Analysis of soluble Heavy Metals		GB18586:2001	PASS
Shore Hardness	HR	ISO7619-1:2004	PASS
Nitrosamines	R ₂ N-N=O	EN71-12:2016	PASS

Precautions

FloorXL products are not suitable for areas subjected to regular and extended exposure to certain solvents, organic dyes or floor maintenance products containing pine oil. For further details please check our Installation/maintenance Guides or contact your FloorXL representative