


# SR Classic SELECT


## Heterogeneous sheet Flooring



SEL1206




SEL1291



SEL1292




SEL1294




SEL1234



SEL1236



SEL1214




SEL1208




SEL1272



SEL1276




SEL1278



SEL1279




SEL1282



SEL1283



SEL1244



SEL1299

# SR Classic SELECT

## Heterogeneous sheet Flooring


### Description

High Specification R9 Resilient Heterogeneous Sheet Flooring

Suitable for use in all Dry areas: Offices, Schools, Libraries, Hospitals and Nursing homes

is a requirement for wear and slip resistance

Available in 2.0mm and 3.0mm thickness



1 PUR

2 Wear Resistant Layer














3 Printed Film

4 Glass Fibre Layer

5 Reinforced Layer

### Technical

SR Classic SELECT is available with the following performance attributes. Please advise your specific requirements so we can offer the corresponding performance level product for your needs

Overall Thickness		GB/T 11982.1 2015	2.0mm 3.0mm
Wear Resistant Layer Thickness		GB/T 11982.1 2015	0.35mm/0.55mm/0.7mm
Roll Dimensions - width		GB/T 11982.1 2015	2.0m
Roll Dimensions - length		GB/T 11982.1 2015	20m
FIRE Performance		GB8624-2012	B1
SLIP RESISTANCE		DIN 51130-2014	R9
Residual Indentation		GB/T11982.1-2015	PASS
Wear Resistance		GB/T11982.1-2015	T LEVEL
Heating Warpage		GB/T11982.1-2015	PASS
Dimensional Stability		GB/T11982.1-2015	PASS
Hazardous Substances Limit		GB18586-2001	PASS
Colour Fastness		GB/T11982.1-2015	Conforms with Standard
Seam Strength		GB/T11982.1-2015	Conforms with Standard

### Precautions

FloorXL products are not suitable for areas subjected to regular and extended exposure to rubber matting, certain solvents, organic dyes or floor maintenance products containing pine oil. Contact with rubber tyres and lighted cigarette butts may also damage the products. For further details please check our Installation/maintenance Guides or contact your FloorXL representative